PORT SIDE

MARK "MAIN FUEL TANK STRAINER" IN 1/2 INCH BLACK LETTERS BOTH SIDES OF AIRPLANE

MARK "STEP PULL OUT" IN 1/2 INCH BLACK LETTERS 2 PLACES PORT SIDE

MARK "SNUG POST SOCKET" IN 1/2 INCH BLACK LETTERS OUTSIDE INSIGNIA WITH 1/2 INCH WIDE ARROW TO SOCKET

INNER VIEW NACELLE

JX-570

MARK "SNUB POST SOCKET" IN 1/2 INCH BLACK LETTERS

MARK "DO NOT PUSH HERE" IN 1/2 INCH BLACK LETTERS 3 PLACES BOTH SIDES OF AIRPLANE.

MARK "STEP PULL OUT" IN 1/2 INCH BLACK LETTERS

MARK AS PER DWG 28E4020

MARK "FUEL UNIT" IN 1/2 INCH BLACK LETTERS BOTH SIDES

MARK IN 1 INCH BLACK NUMBERS ON HULL "3/4 AS SHOWN ON PORT SIDE

STARB'D SIDE

MARK IN 1/2 INCH BLACK LETTERS "WING BOLT" BOTH SIDES

BOTTOM OF DE-ICER BOOT (REF)

INNER VIEW NACELLE

YELLOW
BLUE
WHITE
RED

MARK IN 1 INCH BLACK NUMBERS ON HULL "1 & 2 AS SHOWN ON STARB'D SIDE

JX-570 IS SAMPLE NUMBER ONLY. NUMBERS TO BE PAINTED ON SHIPS AS PER THOSE ASSIGNED BY BRITISH. BLOCK LETTERS (SEE DETAIL BELOW) COLOR - LIGHT SLATE GREY OR BLACK

JX-570

ALL LETTERS 1 INCH TYP

5 (TYP)

NOTE: THIS DRAWING TRACED FROM 28Z9001 ISSUED BY ELIZABETH CITY D.V.N.

DANGER PROPS

PAINT IN RED OVER SPECIFIED CAMOUFLAGE

IN LINE WITH T.E. DEICER BOOT

MARK IN 1 INCH BLACK LETTERS 2 PLACES "NO STEP"

TOP SIDE ONLY

	DULL BLUE
	DULL RED
	EXTRA DARK SEA GRAY
	DARK SLATE GRAY
	WHITE

NOTES

1.) MATERIAL: USE DUPONT CAMOUFLAGE PAINT
   - A-WHITE # 71-001
   - B-DULL BLUE # 71-012
   - C-DULL RED # 71-007
   - D-YELLOW # 71-010
   - E-EXTRA DARK SEA GRAY # 71-19324
   - F-DARK SLATE GRAY # 71-19323
   - G-BLACK # 71-006

2) ALL FOREIGN INSIGNIA & MARKINGS TO BE "BLOCKED OUT" WITH WATER SOLUBLE SOYA PROTEIN OR CASEIN BASE PAINT OR EQUIVALENT.

3) ADD SIX (6) U.S. NATIONAL STAR INSIGNIA LOCATED AS SHOWN ON 28Z5026 USING WATER SOLUBLE SOYA PROTEIN OR CASEIN BASE PAINT OR EQUIVALENT.

4) ON EACH OF THE TEMPORARY STAR INSIGNIA STENCIL THE FOLLOWING INSTRUCTIONS IN SMALL LETTERS "REMOVE BLOCK OUT PAINT BY WASHING WITH A RAG SATURATED WITH WHITE GASOLINE OR MINERAL SPIRITS.

5) ON FABRIC SURFACES DOPED WITH ACETATE BUTERATE DOPE AN ACETATE BUTERATE PIGMENTED DOPE MUST ALSO BE USED. THE COLOR IS TO AGREE WITH PRESENT CAMOUFLAGE COLOR SCHEME.



CONT 91876 LL
MCR 39B

APPROVED FOR TOOLING BY
E. E. Dalton
5-15-43

TOLERANCE OF CAMOUFLAGE PATTERN ±2"

	PBY-5	28Z1025	
ASSY DASH NO.	MODEL	NEXT ASSY	

REQUIREMENTS PER AIRPLANE

SCALE 1/4" = 1'0"

STAMP PART NUMBER WHERE SHOWN

PARTS LIST PER ASSY.: PART No | STOCK | MATERIAL | SPEC | REQ -0 | REQ -2 | REQ -3 | REQ -4 | REQ -5

A C		KRUK	
NAVY NONE	NOTED	3-1-43	
HEAT TREAT	FINISH	DRAFT	CHECK

NAME CAMOUFLAGE MARKING & INSIGNIA

CONSOLIDATED AIRCRAFT CORP SAN DIEGO CALIF

DWG J 28Z5030

R